DATA SHEET



Electric Children Bed

CT8k

LEEX

The **CT8k electric bed** is designed to withstand intensive care procedures in pediatric patients. Providing staff with greater efficiency and ease of handling. Giving safety and compliance to the patient.



CHARACTERISTICS



- **5 movements:** back-rest, knee-rest, trendelenburg, reverse trendelenburg, height adjustment.
- **Design:** aluminum alloy side rail, 12-staff,providing full protection, meets safety standards and provides a comforting feeling for patients.
- **Four wheels with central locking:** 5-inch double-sided casters, smooth and smooth running, durable with central locking.Making its operation easier.
- **Steels and painting**: baosteel from Fortune Global 500 11 Process epoxy painting, ASTM testing antibacterial, paint thickness 0.12 mm, brightness 60°, paint can resist 50 kg impact
- **Folding bed rail:** easy access to the patient.
- **Back-rest adjustment** (75°) and **Knee-rest adjustment** (35°).





HEIGHT ADJUSTMENT



TRENDELENBURG



ANTI-TRENDELENBURG



KNEE-REST



BACK-REST

LEEX

SPECIFICATION

Technical parameters

External size (LxWxH)	1800x780x480-770 mm
Height adjustment	480-770 mm
Mattress platform (LxW)	1890 x 640 mm
Back-rest adjustment	0-75° (±10°)
Knee-rest adjustment	0-35° (±10°)
Trendelenburg	0-12°
Reverse Trendelenburg:	0-12°
Maximum load	250 Kg
Rail height	40 cm
Rail spacing	8,1 cm

Configuration

Standard
5 Movements (back-rest, knee-rest, trendelenburg, reverse trendelenburg, height adjustment) Electric Motor Aluminum alloy side rail with extra protection (1 pc) IV pole (1 pc) Drainage hook (1 pc) 5" Double side castors, central locking (4 pcs)

Additional
Mattress (1580x650x100mm)

LEEX

Components




DESIGN
Aluminum alloy side rail, 12-staff providing full protection and comforting feelings for patients.



WHEELS
5-inch double-sided casters, smooth and smooth running, durable with central locking.



NURSE CONTROL
Hook type nurse control.



BED PLATFORM
Stamping forming platform, smooth surface no welding scar, bearing 250KG load.



BRAKING SYSTEM
Break spring keep qualified after 10,000 times uninterrupted break.



BUMPER COVER
Reduce the impact of the collision, safe and slinky.



IV POLE
Stainless steel column with plastic hook.



DRAINAGE HOOKS
Mobile plastic drainage hooks.

LEEX